

# Low Voltage Power Supply

# 24 Volt

## Xenflex LED & Xen-Flexible LED

These state of the art power supplies incorporate very efficient, low weight toroidal transformers and are equipped to operate with dual input voltages.

### Features

- Input: 120V/277V
- Single Output Secondary Voltage: 24V
- Toroidal transformer
- Transformer can be loaded up to the maximum rating
- Epoxy encapsulated transformer resulting in silent operation, eliminating long term corrosion and rusting at the connections
- Powder coated textured paint finish
- Easy opening case with knock-outs for hardwiring
- Auto resettable In-line primary overload protection
- In-line secondary magnetic breaker to protect against short circuit and overloading
- 50 amp terminal boards on the output for ease of installation
- Labeling and complete operating instructions supplied
- UL listed to U.S. and Canadian safety standards



### 24 Volt Transformers

Cat No.	VA Rating	Primary Voltage	Secondary Voltage	Dimensions (LxWxH)	# of Breakers	Amperage Rating	Weight
XTR-75-24V	75	120/277	24	8.75" x 4.375" x 4.25"	0	-	8 Lbs
XTR-150-24V	150	120/277	24	8.75" x 4.375" x 4.25"	1	7	8 Lbs
XTR-300-24V	300	120/277	24	8.75" x 4.375" x 4.25"	1	12.5	10 Lbs
XTR-600-24V	600	120/277	24	9.5" x 5.375" x 5.125"	1	25	16 Lbs
XTR-900-24V	900	120/277	24	10.5" x 6.125" x 6"	2	20	26 Lbs
XTR-1200-24V	1200	120/277	24	11.625" x 7" x 6"	2	25	26 Lbs